



5-Pack P10 Series UHF

Designed to be fully modular and space efficient,
providing continuous duty operation.

403-512 MHz, 100 Watts Output Power

Frequency Range:	403-450 MHz (UL), 450-512 MHz (UH)
Operating Voltage:	+13.8 VDC
Current Draw:	26 Amperes (Max)
Duty Cycle:	100%
Power Input:	See chart below
Power Output:	100 Watts, set at factory
Spurious & Harmonics:	Meets FCC Requirements
Input/Output Impedance:	50 ohms (Nominal)
Load VSWR Tolerance:	VSWR Protected
Indicator LEDs:	DC On, Low Output, High VSWR, High Temp
Alarm:	Summary Alarm Pin (Open Collector, LOW when Alarm)
Input/Output Connector:	Type 'N' Female
Cooling Method:	Fan Forced Air Over Heat sinks
Operating Temp. Range:	-30° C to +60° C
Storage & Transport:	-40° C to +70° C
Humidity:	80% at +40° C (non-condensing)
Altitude:	10,000 feet maximum

SIZE

Vertical Mounting:	7.0"
Horizontal Mounting:	3.4"
Depth:	19.0"
Weight:	10 pounds

POWER INPUT RANGE

<u>Model Description</u>	<u>Required Power In</u>	<u>Power Output</u>
P10-R1XX1-C7-001	100-200 mW	100 W
P10-R2XX1-C7-001	200-500 mW	100 W
P10-R5XX1-C7-001	500 mW-1 W	100 W
P10-1XX1-C7-001	1-2 W	100 W
P10-2XX1-C7-001	2-5W	100 W
P10-5XX1-C7-001	5-10 W	100 W
P10-10XX1-C7-001	10-20 W	100 W
P10-20XX1-C7-001	20-50 W	100 W

*** XX-Insert the letter definition for the frequency range chosen
FPR-5 Rack Sold Separately.**

Crescend Technologies, LLC · 140 E. State Parkway · Schaumburg, IL 60173
Phone: (800) USA-MADE / (847) 908-5400 Fax: (847) 908-5408 · www.crescendrf.com

These specifications are subject to change without notice.