



## 5-Pack P5 Series UHF

Designed to be fully modular and space efficient,  
providing continuous duty operation.

### General Specifications

Frequency Range:	403-450 MHz (UL), 450-512 MHz (UH)
Current Draw:	13 Amperes (Max)
Operating Voltage:	+13.8 VDC
Duty Cycle:	100%
Power Input:	See chart below
Power Output:	50 Watts, set at factory
Spurious & Harmonics:	Meets FCC Requirements
Input/Output Impedance:	50 ohms (Nominal)
Load VSWR Tolerance:	VSWR Protected
Indicator LEDs:	DC On, Low Output, High VSWR, High Temp
Alarm:	Summary Alarm Pin ( <b>Open Collector, LOW when Alarm</b> )
Input/Output Connector:	Type 'N' Female
Cooling Method:	Fan Forced Air Over Heat sink
Operating Temp. Range:	-30° C to +60° C
Storage & Transport:	-40° C to +70° C
Humidity:	80% at +40° C (non-condensing)
Altitude:	10,000 feet maximum

### SIZE

Vertical Mounting:	7.0"
Horizontal Mounting:	3.4"
Depth:	19.0"
Weight:	10 pounds nominal

### POWER INPUT RANGE

<u>Model Description*</u>	<u>Required Power In</u>	<u>Power Output</u>
P5-R1XX1-C7-001	100-200 mW	50 W
P5-R2XX1-C7-001	200-500 mW	50 W
P5-R5XX1-C7-001	500 mW-1 W	50 W
P5-1XX1-C7-001	1-2 W	50 W
P5-2XX1-C7-001	2-5W	50 W
P5-5XX1-C7-001	5-10 W	50 W
P5-10XX1-C7-001	10-20 W	50 W

\* **XX-Insert the letter definition for the frequency range chosen**

**FPR-5 Rack Sold Separately.**

Crescend Technologies, LLC · 140 E. State Parkway · Schaumburg, IL 60173  
Phone: (800) USA-MADE / (847) 908-5400 Fax: (847) 908-5408 · www.crescendrf.com

These specifications are subject to change without notice.